



System Specifications

- Equipment Name: ION BALL CLEAN 300 II S
- Tank Material: Shock-Proof Reinforced Polyvinyl Chloride (PVC)
- Circulation Mechanism: Submerged Pump
307 LPH (81 GPH) with:
 - Oil Adsorption Material (Coconut Activated Carbon Filter)
 - Nonwoven Fabric Filtration Filter
- Power Supply: 120VAC 6.8W, 60HZ

Usage

- Use with: ION POWER 2000 4.5L (1.2G)
- Operation Time: About 15 – 60min (depends on balls)

You can play right after the oil removal!!

ION

Bowling Ball Oil Extracting Liquid

ION POWER 2000

POWER

2000



The alkaline electrolysis ionic solution permeates the oil on the surface of the ball as well as into the ball, and the surfactant flushes oil and dirt.

Alkaline Electrolysis Ion
X
Surfactant



Just dip the ball in the ION POWER 2000 solution for 15-60 minutes, and wipe the ball with the dry towel.



Recommended to spray ION POWER S when drying the ball after immersion cleaning.



You can use the ball immediately after cleaning because of non-heating degreasing.



Baronbox
20 Liters
30cm x 30cm x30cm

株式会社フェムテック

東京都荒川区西日暮里2-50-5

TEL 03-5615-3232 FAX 03-5615-3233

www.femteh.co.jp

株式会社フェムテック
femtech